



TOKBO HD CCTV / D			نىدىدە لوران بولد ھايك ويۇن ۋ تجويوات شك
مدل	اطلاحات محصول	قیمت(ریال)	تصوير محصول
	Turbo HD - 2&1MP ColorVu		
DS-2CE72KF0T-FS	High quality imaging with 3K, 2960 × 1665 resolution 24/7 color imaging with F1.0 aperture 2.8 mm and 3.6 mm fixed focal lens Up to 40 m white light distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67) High quality audio with audio over coaxial cable, built-in mic	37,400,000	
DS-2CE72HFT-F28	5 MP full time color turret camera 24/7 full color imaging 2.8 mm fixed focal lens Warm supplemental light with 20 m range Clear imaging even against strong back lighting due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).	38,370,000	
DS-2CE10DF0T-F	2 MP full time color bullet camera 24/7 full color imaging Warm supplemental light with 20 m range Clear imaging even against strong back lighting due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS);	32,130,000	ANXISON SOL
DS-2CE12DF3T-FS	High quality imaging with 2 MP, 1920 × 1080 resolution 24/7 color imaging with F1.0 aperture  Clear imaging against strong back light due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images  2.8 mm, 3.6 mm, 6 mm fixed focal lens  Up to 40 m white light distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)  High quality audio with audio over coaxial cable, built-in mic	38,330,000	AKASSAN A
DS-2CE12DF3T-F	High quality imaging with 2 MP, 1920 × 1080 resolution 24/7 color imaging with F1.0 aperture  Clear imaging against strong back light due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images  2.8 mm, 3.6 mm, 6 mm fixed focal lens  Up to 40 m white light distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)  High quality audio with audio over coaxial cable,	33,470,000	HICKSON
DS-2CE10DF3T-FS	High quality imaging with 2 MP, 1920 × 1080 resolution 24/7 color imaging with F1.0 aperture  Clear imaging against strong back light due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images 2.8 mm, 3.6 mm fixed focal lens  Up to 20 m white light distance for bright night imaging High quality audio with audio over coaxial cable, built-in mic One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)	34,070,000	MINISON

DS-2CE70DF3T-PF	High quality imaging with 2 MP, 1920 × 1080 resolution 24/7 color imaging with F1.0 aperture Clear imaging against strong back light due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images 2.8 mm, 3.6 mm, 6 mm fixed focal lens Up to 20 m white light distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS)	26,980,000	O No.
DS-2CE72DF3T-F	High quality imaging with 2 MP, 1920 × 1080 resolution 24/7 color imaging with F1.0 aperture  Clear imaging against strong back light due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images 2.8 mm, 3.6 mm, 6 mm fixed focal lens  Up to 40 m white light distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)	25,410,000	
DS-2CE70DFT-PF	High quality imaging with 2 MP, 1920 × 1080 resolution 24/7 color imaging with F1.0 aperture  Clear imaging against strong back light due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images Up to 20 m white light distance for bright night imaging  High quality audio with audio over coaxial cable, built-in mic One port for four switchable signals (TVI/AHD/CVI/CVBS)	Call	
DS-2CE70DF0T-PF	2 MP ColorVu Indoor Fixed Turret Camera High quality imaging with 2 MP, 1920 × 1080 resolution 24/7 color imaging with F1.0 aperture 3D DNR technology delivers clean and sharp images Up to 20 m white light distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) DWDR;BLC;HLC;Global	Call	
	Turbo HD - 2MP		
DS-2CE16D0T-EXIF	High quality imaging with 2 MP, 1920 × 1080 resolution 2.8 mm, 3.6 mm fixed lens Up to 20 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP66)	12,980,000	
DS-2CE16D0T-EXIPF	High quality imaging with 2 MP, 1920 × 1080 resolution 2.8 mm, 3.6 mm fixed lens Up to 20 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP66)	Call	
DS-2CE16D0T-ITPF	2 MP, 1920 × 1080 resolution 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) Smart IR, up to 25 m IR distance IP67	Call	
DS-2CE16D0T-ITPFS	2 MP coaxial audio camera Enhancing safety with discreet and economical built-in microphone Transmits audio over the coaxial cable EXIR 2.0: advanced infrared technology with 25 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	16,390,000	
DS-2CE16D0T-ITF	2 MP Fixed Mini Bullet Camera 2 MP bullet camera Smart IR: up to 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	Call	

DS-2CE16D3T-ITF	2 MP bullet camera  Strong night performance, capturing images in ultra-low light down to 0.005 lux Clear imaging even against strong back lighting due to 120 dB true WDR technology  3D DNR technology delivers clean and sharp images EXIR 2.0: advanced infrared technology with 30 m IR distance  Water and dust resistant (IP67)  4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	21,660,000	
DS-2CE16D3T-IT3F	2 MP bullet camera Strong night performance, capturing images in ultra-low light down to 0.005 lux Clear imaging even against strong back lighting due to 120 dB true WDR technology 3D DNR technology delivers clean and sharp images EXIR 2.0: advanced infrared technology with 50 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	22,240,000	
DS-2CE16D0T-ITFS	2 MP coaxial audio camera Enhancing safety with discreet and economical built-in microphone Transmits audio over the coaxial cable EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67) DWDR/BLC/HLC/Global	17,620,000	
DS-2CE17D0T-IT1F	High quality imaging with 2 MP, 1920 × 1080 resolution 2.8 mm, 3.6 mm, 6 mm fixed focal lens Up to 30 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)	18,050,000	Arran A
DS-2CE17D0T-IT3F	High quality imaging with 2 MP, 1920 × 1080 resolution 2.8 mm, 3.6 mm, 6 mm fixed focal lens Up to 40 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)	23,160,000	out com
DS-2CE76D3T-ITPF	2 MP Ultra Low Light Indoor Fixed Turret Camera 2 MP turret camera Strong night performance, capturing images in ultra-low light down to 0.005 lux Clear imaging even against strong back lighting due to 120 dB true WDR technology  3D DNR technology delivers clean and sharp images EXIR 2.0: advanced infrared technology with 30 m IR distance 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).	17,420,000	And the same of th
DS-2CE76D3T-ITPF	2 MP Ultra Low Light Indoor Fixed Turret Camera 2 MP turret camera Strong night performance, capturing images in ultra-low light down to 0.005 lux Clear imaging even against strong back lighting due to 120 dB true WDR technology 3D DNR technology delivers clean and sharp images EXIR 2.0: advanced infrared technology with 30 m IR distance 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).	23,840,000	
DS-2CE76D0T-ITMF	2 MP Ultra Low Light Indoor Fixed Turret Camera 2 MP turret camera Strong night performance, capturing images in ultra-low light down to 0.005 lux Clear imaging even against strong back lighting due to 120 dB true WDR technology 3D DNR technology delivers clean and sharp images EXIR 2.0: advanced infrared technology with 30 m IR distance 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).	16,440,000	The same of the sa

DS-2CE76D0T-EXIPF	High quality imaging with 2 MP, 1920 × 1080 resolution 2.8 mm, 3.6 mm fixed lens Up to 20 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS)	13,390,000	TON ESTA
DS-2CE76D0T-ITPF	2 MP, 1920 × 1080 đĞEŽůZ⊖Žn 2.8 mm, 3.6 mm, 6 mm ĮdžĞĚ focal lens 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) Smart IR, up to 20 m IR distance	11,250,000	Maria
DS-2CE76D0T-ITMFS	2 MP, 1920 × 1080 resolution DWDR/BLC/HLC/Global up to 30 m IR distance Audio over coaxial cable, built-in mic 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) IP67	18,810,000	PARKER
DS-2CE76D0T-ITPFS	2 MP Audio Indoor Fixed Turret Camera 2 MP coaxial audio camera Enhancing safety with discreet and economical built-in microphone Transmits audio over the coaxial cable EXIR 2.0: advanced infrared technology with 20 m IR distance 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	14,840,000	THE GIA
DS-2CE78D0T-IT3FS	2 MP coaxial audio camera  Enhancing safety with discreet and economical built-in microphone Transmits audio over the coaxial cable  EXIR 2.0: advanced infrared technology with 40 m IR distance Water and dust resistant (IP67)  4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	Call	1000
	2MP VariFocal		
DS-2CE16D0T-VFIR3F	2 MP varifocal bullet camera 2.8 mm to 12 mm varifocal lens Up to 40 m IR distance for bright night imaging Water and dust resistant (IP66) One port for four switchable signals (TVI/AHD/CVI/CVBS)	Call	
DS-2CE56D0T-VFIR3F	2 MP varifocal dome camera 2.8 mm to 12 mm varifocal lens Up to 40 m IR distance for bright night imaging Water and dust resistant (IP66) One port for four switchable signals (TVI/AHD/CVI/CVBS)	32,240,000	
	Turbo HD - 5MP		
DS-2CE16H0T-ITF	5 MP Bullet Camera • 5 Megapixel high-performance CMOS • Analog HD output, up to 5MP resolution • True Day/Night • OSD menu, 2D DNR, DWDR • EXIR technology, up to 20m IR distance • IP67 • 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) • Up the Coax(HIKVISION-C)	19,470,000	Name of the second
DS-2CE16H0T-ITPF	5 MP Bullet Camera 5 Megapixel high-performance CMOS  • Analog HD output, up to 5MP resolution • True Day/Night  • OSD menu, 2D DNR, DWDR • EXIR technology, up to 20m IR distance  • IP67 • 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)  • Up the Coax(HIKVISION-C)	Call	Many 9
DS-2CE16H0T-ITPFS	5 MP, 2560 × 1944 resolution Digital WDR  2.8 mm, 3.6 mm, 6 mm fixed focal lens Smart IR, up to 25 m IR distance Audio over coaxial cable, built-in mic  4 in 1 video output (switchable TVI/AHD/CVI/CVBS) IP67,Material	20,770,000	0

DS-2CE16H0T-ITFS	5 MP Audio Fixed Mini Bullet Camera 5 MP coaxial audio camera Enhanced safety with discreet and economical built-in microphone Transmit audio over coaxial cable EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	23,050,000	
DS-2CE17H0T-IT1F	5 MP Fixed Bullet Camera  High quality imaging with 5 MP, 2560 × 1944 resolution Up to 30 m IR distance for bright night imaging  One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)  DWDR/BLC/HLC/Global	Call	
DS-2CE17H0T-IT3F	5 MP Fixed Bullet Camera  High quality imaging with 5 MP, 2560 × 1944 resolution Up to 40 m IR distance for bright night imaging  One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)  DWDR/BLC/HLC/Global	23,300,000	
DS-2CE17H0T-IT3FS	5 MP Audio Fixed Bullet Camera High quality imaging with 5 MP, 2560 × 1944 resolution 2.8 mm, 3.6 mm, 6 mm fixed focal lens Up to 40 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67) High quality audio with audio over coaxial cable, built-in mic DWDR;BLC;HLC;Global	29,790,000	
DS-2CE17H0T-IT5F	5 MP Fixed Bullet Camera  High quality imaging with 5 MP, 2560 × 1944 resolution Up to 80 m IR distance for bright night imaging  One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)  DWDR/BLC/HLC/Global	Call	
DS-2CE16H0T-IT3ZF	5 MP Bullet Camera • 5 Megapixel high-performance CMOS • Analog HD output, up to 5MP resolution • 2.7-13.5mm motorized vari-focal lens • True Day/Night • OSD menu, 2D DNR, DWDR • EXIR technology, up to 40m IR distance • IP67 • PoC.at • Up the Coax(HIKVISION-C)	Call	
DS-2CE76H0T-ITPF	5 MP turret camera EXIR 2.0: advanced infrared technology with 20 m IR distance 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS) DWDR/BLC/HLC/Global	Call	6
DS-2CE76H0T-ITMF	5 MP turret camera EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	21,440,000	
DS-2CE76H0T-ITPFS	5 MP Audio Fixed Turret Camera 5 MP coaxial audio camera Enhanced safety with discreet and economical built-in microphone Transmit audio over coaxial cable EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	Call	
DS-2CE76H0T-ITMFS	5 MP Audio Fixed Turret Camera 5 MP coaxial audio camera Enhanced safety with discreet and economical built-in microphone Transmit audio over coaxial cable EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	24,290,000	

DS-2CE78H0T-IT1F	5 MP turret camera EXIR 2.0: advanced infrared technology with 20 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	Call	6
DS-2CE78H0T-IT3F	5 MP turret camera EXIR 2.0: advanced infrared technology with 40 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	Call	
DS-2CE78H0T-IT1F	5 MP Turret Camera • 5 Megapixel high-performance CMOS • 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) • True Day/Night • OSD menu, 2D DNR, DWDR • EXIR technology, up to 20m IR distance • IP67 weatherproof • 2560 × 1944 resolution • Up the Coax(HIKVISION-C)	19,470,000	
DS-2CE56H0T-IT3F	5 MP Turret Camera • 5 Megapixel high-performance CMOS • 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) • True Day/Night OSD menu, 2D DNR, DWDR • EXIR technology, up to 40m IR distance IP67 weatherproof • 2560 × 1944 resolution • Up the Coax(HIKVISION-C)	Call	
DS-2CE56H0T-IT3ZF	5MP-Lens: 2.7-13.5mm/F1.2-Horizontal Field of View: 95.7°- 29.1°Resolution: 2560×1944px  Image sensor: 5 MP CMOS image sensor-Function: day/night ICR-DNR -D-WDR AGC-BLC-Smart IR-Mirror-Min. Illumination: 0.01Lx-IR distans: 40m-Power supply: DC 12VDC  Power consumption: max. 6.3W-Dimensions: 123.86×134.3×110.11mm  Weight: 580g-Temperature of work: -40°C~60°C	Call	
	Turbo HD - 8MP		
DS-2CE78U8T-IT3	4K Ultra-Low Light Turret Camera 8.29 Megapixel high-performance CMOS Ultra-low light 3840 × 2160 resolution 2.8 mm, 3.6 mm, 6 mm fixed focal lens 120 dB true WDR, 3D DNR EXIR 2.0, smart IR, up to 60m IR distance IP67 Up the Coax(HIKVISION-C)	63,870,000	
DS-2CE18U8T-IT3	K Ultra-Low Light Bullet Camera • 8.29 Megapixel high-performance  CMOS  • Ultra-low light • 3840 × 2160 resolution • 2.8 mm, 3.6 mm, 6 mm  fixed focal lens  • 120 dB true WDR, 3D DNR • EXIR 2.0, smart IR, up to 60m IR  distance	Call	
	Turbo HD DVR (HQHI)		
DS-7204HQHI-K1	4 Turbo HD/AHD/Analog interface input, 4-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface, CH01: 3MP @ 15fps, CH02-04:1920×1080P @15 fps/ch, support CVBS output, standalone 1U case	Call	

IDS-7204HQHI-M1/S	4 channels and 1 HDD 1U AcuSense DVR False alarm reduction through human and vehicle target classification based on deep learning Efficient H.265 pro+ compression technology Encoding ability up to 1080p @ 15 fps 5 signals input adaptively (HDTVI/AHD/CVI/CVBS/IP) Up to 6 network cameras can be connected.	46,520,000	
DS-7208HQHI-K1	8 Turbo HD/AHD/Analog interface input, 8-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface, CH01 & 02: 3MP @ 15fps, CH03-08:1920×1080P @15 fps/ch, , support CVBS output, standalone 1U case	Call	
IDS-7208HQHI-M1/S	8 channels and 1 HDD 1U AcuSense DVR False alarm reduction through human and vehicle target classification based on deep learning Efficient H.265 pro+ compression technology Encoding ability up to 1080p @ 15 fps 5 signals input adaptively (HDTVI/AHD/CVI/CVBS/IP) Up to 12 network cameras can be connected.	71,290,000	
DS-7116HQHI-K1	Support H.265 Pro+/H.265 Pro/H.265 video compression Support HDTVI/AHD/CVI/CVBS/IP video input Audio via coaxial cable Max.  6/12/24 IP cameras input (up to 6 MP)  Max. 800 m for 1080p and 1200 m for 720p HDTVI signal transmission  Up to 6TB capacity per HDD	Call	
DS-7216HQHI-K1	16 Turbo HD/AHD/Analog interface input, 16-ch video&1-ch audio input, <b>H.265/H.265+</b> compression, 1 SATA interface,CH01-04: 3MP @ 15fps, CH05-16:1920×1080P @15 fps/ch, <b>4K UHD output</b> , support CVBS output, standalone 1U case	121,800,000	
DS-7216HQHI-K2	16-ch 1080p 1U H.265 POC DVR 16 channels and 2 HDDs 1U DVR Efficient H.265 pro+ compression technology Encoding ability up to 1080p @ 15 fps 5 signals input adaptively (HDTVI/AHD/CVI/CVBS/IP) Up to 24 network cameras can be connected Transmits both HDTVI video and power over the same coaxial cable	Call	
iDS-7216HQHI-M1/S	16-ch 1080p 1U H.265 AcuSense DVR 16 channels and 1 HDD 1U AcuSense DVR False alarm reduction through human and vehicle target classification based on deep learning Efficient H.265 pro+ compression technology Encoding ability up to 1080p @ 15 fps 5 signals input adaptively (HDTVI/AHD/CVI/CVBS/IP) Up to 8 network cameras can be connected	124,090,000	
iDS-7216HQHI-M2/S	16-ch 1080p 1U H.265 AcuSense DVR 16 channels and 2 HDDs 1U AcuSense DVR False alarm reduction through human and vehicle target classification based on deep learning Efficient H.265 pro+ compression technology Encoding ability up to 1080p @ 15 fps 5 signals input adaptively (HDTVI/AHD/CVI/CVBS/IP) Up to 8 network cameras can be connected	Call	
iDS-7232HQHI-M2/S	Deep learning-based motion detection 2.0 for all analog channels  Deep learning-based perimeter protection  Efficient H.265 pro+ compression technology  Encoding ability up to 1080p @ 15 fps  5 signals input adaptively (HDTVI/AHD/CVI/CVBS/IP)  Up to 40 network cameras can be connected	248,310,000	1000

DS-7232HQHI-K2	32 Turbo HD/AHD/Analog interface input -H.265+/H.265/H.264+/H.264 encoding for the main stream, and H.265/H.264 for the sub-stream of analog cameras - Selfadaptive HDTVI/HDCVI/AHD/CVBS signal input - Connectable to H.265+/H.265/H.264+/H.264 IP cameras - Full channel recording at up to 4 MP lite resolution - HDMI output at up to 4K (3840 × 2160) resolution - Long distance transmission over UTP and coaxial cable: max. 800m for 1080p and 1200m for 720p HDTVI signal -16-ch synchronous playback	267,320,000	
	Turbo HD DVR (HUHI)		
DS-7204HUHI-K1	4 Turbo HD/AHD/Analog interface input, 4-ch video&4-ch audio input, 1 SATA interface, H.265/H.265+ compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920×1080P: 25(P)/30(N) fps/ch, alarm I/O: 4/1, support CVBS output, standalone 1U case	67,720,000	Tal I
iDS-7204HUHI-M1/S	4 channels and 1 HDD 1U AcuSense DVR False alarm reduction by human and vehicle target classification based on deep learning Efficient H.265 pro+ compression technology Encoding abilty up to 8 MP @ 8 fps, 5 MP @ 12 fps 5 signals input adaptively (HDTVI/AHD/CVI/CVBS/IP) Up to 8 network cameras can be connected.	74,720,000	
iDS-7208HUHI-M1/S	8 channels and 1 HDD 1U AcuSense DVR False alarm reduction by human and vehicle target classification based on deep learning Efficient H.265 pro+ compression technology Encoding abilty up to 8 MP @ 8 fps, 5 MP @ 12 fps 5 signals input adaptively (HDTVI/AHD/CVI/CVBS/IP) Up to 16 network cameras can be connected.	120,610,000	
DS-7208HUHI-K1	8 Turbo HD/AHD/Analog interface input, 8-ch video&4-ch audio input, 1 SATA interface, <b>H.265/H.265+</b> compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920×1080P: 25(P)/30(N) fps/ch, 4K UHD output, alarm I/O: 8/4, support CVBS output, standalone 1U case	Call	Tal I
DS-7216HUHI-K2	16 Turbo HD/AHD/Analog interface input, 16-ch video&4-ch audio input, 2 SATA interfaces, H.265/H.265+ compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920×1080P: 25(P)/30(N) fps/ch, 4K UHD output, alarm I/O: 16/4, support CVBS output, 380 1U case	218,730,000	
DS-7216HUHI-M2/S	Deep learning-based motion detection 2.0 for all analog channels Deep learning-based perimeter protection  Efficient H.265 pro+ compression technology Encoding abilty up to 8 MP  @ 8 fps, 5 MP @ 12 fps 5 signals input adaptively  (HDTVI/AHD/CVI/CVBS/IP) Up to 32 network cameras can be connected	224,090,000	
DS-7316HUHI-F4/N	Supports HD-TVI, AHD, and Analog Cameras Supports Up to 6/10/18-ch 8 MP IP Cameras Transmission Over UTP and Coaxial Cable H.264+ Compression Recording at Up to 3 MP Resolution HDMI 2 Output at Up to 4K (3840 × 2160) Resolution 4/8/16-ch Synchronous Playback Smart Search for Efficient Playback	447,270,000	<u> </u>
	Turbo HD DVR Built in PoC Series		
DS-7204HUHI-K1/P	4 Turbo HD/AHD/Analog interface input, 4-ch video&4-ch audio input, 1 SATA interface, <b>H.265/H.265+</b> compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920×1080P: 25(P)/30(N) fps/ch, alarm I/O: 4/1, support CVBS output, standalone 1U case, built-in PoC	67,470,000	

DS-7208HUHI-K2/P	8 Turbo HD/AHD/Analog interface input, 8-ch video&4-ch audio input, 2 SATA interfaces, H.265/H.265+ compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920×1080P: 25(P)/30(N) fps/ch, 4K UHD output, alarm I/O: 8/4, support CVBS output, 380 1U case, built-in PoC  Turbo HD DVR 1080p/3Mp/5Mp / 8MP Built	Call In PoC	
DS-7204HTHI-K1	4-ch, RCA (2.0 Vp-p, 1 K $\Omega$ )-4-chBNC interface (1.0 Vp-p, 75 $\Omega$ ), supporting coaxitron connection-2-ch-Up to 8 MP resolution, Supports H.265+/H.265/H.264+/H.264 IP cameras-VGA: 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz HDMI: 1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz-Video Bit Rate: -32 Kbps to 16 Mbps-Stream Type: VidVideo, Video & Audioeo, Video & Audio-Two-way Audio: 1-ch, RCA (2.0 Vp-p, 1 K $\Omega$ ) (using the 1st audio input)-Audio Output: 1-ch, RCA (Linear, 1 K $\Omega$ )-Audio Bit Rate: -64 Kbps	Call	
DS-7208HTHI-K2	4K H265+ TURBO HD DVR-4-ch, RCA (2.0 Vp-p, 1 KΩ)-Video Compression: H.265+/H.265/H.264+/H.264-Analog Video Input: 8-ch,BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection Analog and HD-TVI video input: 8 MP, 5 MP, 4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25 IP Video Input: 4-ch,Up to 8 MP resolution,Supports H.265+/H.265/H.264+/H.264 IP-Interface Type: 2 SATA interfacesCapacity: Up to 8 TB capacity for each disk-Alarm Input: 8-Alarm Output: 4	Call	